

Model: VODEVIL BEIGE

Size: 7.9" x 7.9" (20x20 cm)


Thickness: .31" (8 mm)

Material type: PORCELAIN



| Technical Characteristics | | Reference standard |
|---|--|--------------------------|
| Manufacture process | Single-firing | Dry pressed ceramic tile |
| Thickness (mm.) | 8 | UNE EN ISO 10545 Part 2 |
| Length, width, thickness, side straightness, orthogonality, flatness. | Conforms to the requisites applicable to each model as defined in standard UNE-EN 14411 for Group B Ia | UNE EN ISO 10545 Part 2 |
| Water absorption | E < 0,5 % | UNE EN ISO 10545 Part 3 |
| Flexion resistance N/sq. mm. and breaking strength | > 35 > 1300 | UNE EN ISO 10545 Part 4 |
| Resistance to surface abrasion (Glazed tiles) | 3 | UNE EN ISO 10545 Part 7 |
| Lineal thermic dilatation | < 9*10 ⁻⁶ /° C | UNE EN ISO 10545 Part 8 |
| Thermic impact resistance | It stands the test | UNE EN ISO 10545 Part 9 |
| Cracking resistance | It stands the test | UNE EN ISO 10545 Part 11 |
| Frost resistance | It stands the test | UNE EN ISO 10545 Part 12 |
| Slip resistance | Class 1 | UNE ENV 12633:2003 |

| Chemical resistance | | |
|-------------------------------------|------------------|--------------------------|
| Domestic cleaning products | Type GA | UNE EN ISO 10545 Part 13 |
| Swimming pool salt | Type GA | |
| Acids and bases (low concentration) | Minimum Type GLB | |
| Stains resistance | Minimum Type 4 | UNE EN ISO 10545 Part 14 |

| CE Marking | |
|---|-------------------------------|
|  | CE Declaration of performance |
| | Nº 001VV2013 |