

Model: MEDIX-PR BLANCO


Size: 17.1" x 17.1" (43,5x43,5 cm)

Thickness: .37" (9.5 mm)

Material type: PORCELAIN

| Technical Characteristics   |  | Reference standard       |
|---|--|--------------------------|
| Manufacture process   | Single-firing  | Dry pressed ceramic tile |
| Thickness (mm.)   | 9.5  | UNE EN ISO 10545 Part 2  |
| Length, width, thickness, side straightness, orthogonality, flatness. | Conforms to the requisites applicable to each model as defined in standard UNE-EN 14411 for Group B Ia | UNE EN ISO 10545 Part 2  |
| Water absorption  | E < 0,5 %  | UNE EN ISO 10545 Part 3  |
| Flexion resistance N/sq. mm. and breaking strength                    | > 35<br>> 1300   | UNE EN ISO 10545 Part 4  |
| Resistance to surface abrasion (Glazed tiles)                         | -  | UNE EN ISO 10545 Part 7  |
| Lineal thermic dilatation   | < 9*10 <sup>-6</sup> /° C  | UNE EN ISO 10545 Part 8  |
| Thermic impact resistance   | It stands the test   | UNE EN ISO 10545 Part 9  |
| Cracking resistance   | It stands the test   | UNE EN ISO 10545 Part 11 |
| Frost resistance  | It stands the test   | UNE EN ISO 10545 Part 12 |
| Slip resistance   | -  | UNE ENV 12633:2003       |

| Chemical resistance                 |                  |                          |
|-------------------------------------|------------------|--------------------------|
| Domestic cleaning products          | Type GA          | UNE EN ISO 10545 Part 13 |
| Swimming pool salt                  | Type GA          |                          |
| Acids and bases (low concentration) | Minimum Type GLB |                          |
| Stains resistance                   | Minimum Type 4   | UNE EN ISO 10545 Part 14 |

| CE Marking  |                               |
|---|-------------------------------|
|  | CE Declaration of performance |
|   | Nº 001VV2013                  |